

## Eco and energy saving

Power Consumption (Standby Mode) 0.3 W (When "Remote Start" is set to "Off")

Power Consumption (Networked Standby Mode) 0.5 W (LAN) (when "Remote Start" is set to "On") When a LAN terminal is not connected, it becomes a low power consumption mode (0.5 W)

Standby Mode Activated After about 10 Minutes

## Interface

Input and Output Terminals HDMI (TWO INPUTS) - Digital RGB/Y Pb/Cb Pr/Cr, IR IN - Minijack, LAN - RJ45, 10Base-T/100BASE-TX, REMOTE - RS-232C, D-sub 9-pin (male), TRIGGER - Minijack, DC 12 V Max. 100 mA, USB - Type A, DC 5 V, Max. 500 mA

## Power

Power Consumption 295 W

Power Requirement AC 100 V to 240 V, 50/60 Hz

Acoustic noise 24 dB

## Size & Weight

Dimensions (W x H x D) 18.13" x 7.88" x 18.59"

Weight Approx. 28 lb (13 kg)

## Accessibility

Screen Reader Yes

## Display

Display Resolution 720 x 576/50p, 720 x 480/60p, 1280 x 720/50p, 1280 x 720/60p, 1920 x 1080/50i, 1920 x 1080/60i, 1920 x 1080/24p, 1920 x 1080/50p, 1920 x 1080/60p, 1920 x 1080/120p, 3840 x 2160/24p, 3840 x 2160/25p, 3840 x 2160/30p, 3840 x 2160/50p, 3840 x 2160/60p, 4096 x 2160/24p, 4096 x 2160/25p, 4096 x 2160/30p, 4096 x 2160/50p, 4096 x 2160/60p

Display System 4K SXRD™ panel, projection system

Light source Laser diode

Picture processor X1™ Ultimate for projector

## Hardware

Projection lens zoom / focus Manual (Approx. x1.60) / Manual

## Operating Conditions

Operating temperature / humidity 41 °F to 95 °F (5 °C to 35 °C) / 20% to 80% (no condensation)

Storage temperature / humidity 14 °F to +140 °F (-10 °C to +60 °C) / 20% to 80% (no condensation)

## Video Features

Color Light Output 2000 lm

**Light Output** 2000 lm

## **General Features**

**Contrast Ratio** ∞: 1 (Dynamic Contrast)

**Effective Imager Size** 0.61 in x 3

**Effective pixels** 24,883,200 (3840 x 2160 x 3) pixels

**Projection lens shift** Manual, Vertical +/- 71%, Horizontal +/- 25%

**Throw ratio** 1.38:1 to 2.21:1